



(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 511 853 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
10.12.1997 Bulletin 1997/50

(51) Int. Cl.⁶: **A61L 9/03**

(21) Application number: **92303879.8**

(22) Date of filing: **29.04.1992**

(54) Apparatus for emitting a chemical agent

Anlage zur Abgabe von Chemikalien

Appareil pour l'émission d'un agent chimique

(84) Designated Contracting States:
AT BE CH DE DK ES FR GB GR IT LI LU NL PT SE

• Hammond, Geoffrey Robert
Hull HU3 0LG (GB)

(30) Priority: **01.05.1991 GB 9109442**

(43) Date of publication of application:
04.11.1992 Bulletin 1992/45

(73) Proprietor:
RECKITT & COLMAN PRODUCTS LIMITED
London W4 2RW (GB)

(74) Representative:
Sanderson, Nigel Paul et al
Group Patents Department,
Reckitt & Colman plc,
Dansom Lane
HULL HU8 7DS (GB)

(72) Inventors:
• Gillett, Colin
Lancashire, WN 4 9SL (GB)
• Hampshire, Michael John
Salford (GB)

(56) References cited:
EP-A- 0 296 807 EP-A- 0 334 785
GB-A- 1 123 922 GB-A- 2 057 884
GB-A- 2 097 257 GB-A- 2 117 639
GB-A- 2 139 895 GB-A- 2 195 250

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 511 853 B1

Description

This invention relates to an apparatus for emitting a chemical agent and particularly but not exclusively to an apparatus for emitting a fragrance or an insecticide.

It is known to provide a fragrance in gel form in a plastics moulding sealed by a temperature sensitive semi-permeable membrane. A 1.32 watt heater consisting of a thin metallic helical filament wound on a fibrous core is provided in the moulding. The heater produces a temperature of approximately 55°C at the base of the gel container. When heated the semi-permeable membrane acts to emit the fragrance. However, the amount of fragrance emitted per unit time may not be varied by this known device.

The present invention has been made from a consideration of this problem.

According to the present invention there is provided an apparatus for releasing a chemical agent, said apparatus having or receiving a container for the chemical agent, at least a part of said container being operable to release the chemical agent, said part being temperature sensitive wherein the apparatus comprises heater means for heating the container and means for varying the heat supplied to the container so as to vary the emission of the chemical agent, characterised in that the means for varying the heat supplied to the container comprises at least two relatively movable co-operating parts, one part comprising and/or secured to electric heater means, which part defines a base portion, and the other part comprising and/or secured to the container, wherein the electric heater means is embedded in said base portion.

The two co-operating parts may comprise screw threads.

The heater means may comprise at least one resistor which may be in series with a light output device. The light output device may also act as a fuse.

Means may be provided, for example on the part of the apparatus comprising the heater means, for indicating the distance between the heater means and the container. This may consist of a marking such as a scale or more preferably a triangular shaped marking.

The apparatus may comprise an absorbent material in order to absorb any chemical agent which may leak from the container.

The container may comprise any suitable chemical agent, preferably in a fluid form, such as at least one of a fragrance or an insecticide.

In order that the invention may be more readily understood a specific embodiment thereof will now be described by way of example only with reference to the accompanying drawings in which:-

Fig. 1 is a cross sectional view of one apparatus in accordance with the invention;

Fig. 2 is a plan view of the apparatus of Fig. 1;

Fig. 3 is a plan view of the heater means of the apparatus of Figs. 1 and 2; and

Fig. 4 is a circuit diagram of the heater means of Fig. 3.

Referring to the drawings an apparatus 10 for emitting a chemical agent comprises a housing made substantially of 50% glass-filled, high impact nylon 6 plastics. The housing has a lower part 12 having a cylindrical body 14. Live, neutral and earth electrical pins 16, 18, 20 extend from the body 14 in a manner conventional for a United Kingdom 240V a/c mains powered domestic electrical appliance. The live pin 16 and neutral pin 18 are connected to the circuitry of a heating means 22 which is embedded about 2 mm below the surface 24 of the cylindrical body 14. The circuitry of the heater means 22 is shown in Fig. 4. The circuit comprises two 15K ohm resistors in series with a light emitting diode (LED) 26. Preferably the tails from the resistors are not cut short and large oversized crimps are used thus spreading more metal in the hot zone increasing dissipation and providing more uniform heating. A diode is provided across the LED in the opposing polarity to the LED. The provision of two 15k ohm resistors rather than one 30 ohm resistor is considered advantageous in that this doubles the power dissipation and likewise increases heat generated by doubling the element area. Further the second resistor provides a convenient connection to one of the pins of the LED without substantially increasing the cost. Failure of a single component to a short circuit will also not provide excessive current.

The presence of an operating indicator light via the LED is considered advantageous. The current required by the heater for 240 v a/c operation is about 8 mA. As this falls within the normal operating range of LEDs the LED can conveniently be incorporated into the circuit. Furthermore the LED is designed with a fine filamentary contact to the semiconductor surface and on excessive current overload the LED should fail to an open circuit condition thereby acting as a fuse. It is considered that a separate fuse will not be necessary.

The LED produces light only on the forward conduction cycle, and typically will drop about 2.5 volts. Hence at 8 mA the power dissipation for the forward half cycle is 10 mWatts. On the reverse cycle the same current of 8 mA will flow and a voltage of about 6 volts is likely, giving a power dissipation of 24 mWatts. The total dissipation is, therefore, 34 mWatts, and is within the capabilities of most of the larger 3mm diameter LEDs, which are typically rated at 40 mWatts. A further diode is preferably used to take the reverse current with a volts drop of say 1 volt giving a reverse dissipation of only 4 mWatts. The further diode allows a more efficient LED to be used to increase the light output. However, the extra diode component must be fitted the correct way round in relation to the orientation of the LED, the direction of which is irrelevant as regards the live neutral.

An upstanding wall 28 is provided around the periphery of the cylindrical body 14. A screw thread is provided on the exterior surface of the upstanding wall 28.

The upper part 32 of the apparatus comprises an aesthetically pleasing hollow cover 34, the cover 34 having a depending wall 38. Perforations 36 are provided in the cover for the release of the fragrance. Two spaced apart members 40, 42 extend inwardly from the cover 34. A screw thread 44 is provided on the interior of the depending wall 38 for cooperation with the screw thread of the upstanding wall 28 such that the upper and lower parts 12, 32 may be moved relative to each other in a controlled manner by way of a twisting movement.

A right angled triangular marking 30 is provided on one part of the exterior surface of the cover 34. The two perpendicular sides of the triangle 30 extend vertically and horizontally in the orientation of the apparatus as illustrated. When fully engaged the vertical line of the triangular mark 30 is in line with the LED. On rotation of the cover a smaller area of the triangle is aligned with the LED.

A polypropylene container 46 comprises a cylindrical housing 48 having a flange extending outwardly from the top of the cylindrical housing 48. A temperature sensitive semi-permeable membrane 50 is provided across the top of the cylindrical housing 48. In use the membrane 50 is protected from physical damage by the cover 34. About 6ml of a liquid fragrance are provided in the cylindrical housing 48. In normal use this amount of fragrance is estimated to last for about 30 days after which time the container is replaced. Fine capillary grooves (not shown) are provided on the internal sides of the container 46 so that the liquid fragrance will rise to wet the membrane, so enabling the emission of fragrance even when the liquid is not in contact with the membrane's surface.

In use, the apparatus is plugged into an electricity supply socket, such as a wall mounted socket, by way of the electrical pins 16, 18, 20. This activates the heating circuit and the LED will light. The heat supplied by the dissipation of heat from the resistors in the circuit will heat the base of the container 46 and then the fragrance and semi-permeable membrane. As the semi-permeable membrane is temperature sensitive the heating of the membrane will allow release of the liquid fragrance.

The rate of release of the liquid fragrance may be controlled by moving the base of the container 46 relative to the heater.

When fully engaged the container 46 is in intimate contact with the heated surface 24 of the cylindrical body 14. As the container 46 is unscrewed a gap appears between the heater and the base and this progressively increases in a controlled manner, thereby increasing the heat losses and reducing the temperature of the fragrance housed in the capsule. Furthermore the separation between the heater and the cylinder and thus the degree of heating and fragrance emission is indicated by the amount of the triangular

mark lined up with the LED.

In the apparatus shown the cylinder is heated by the dissipation of about 2 watts to a temperature in the region of 40°C. At this temperature the release of the fragrance through the membrane is appreciable.

With the apparatus illustrated the rate of the release of fragrance is considered to approximately double for every 10°C rise in temperature.

It is to be understood that the above described embodiment is by way of illustration only. Many modifications and variations are possible.

Additional ventilation may be provided to the heated surface, for example by providing apertures on opposite sides of the cover in order to increase air flow. If the apparatus is to be mounted vertically the apertures are preferably provided at the top and base of the apparatus.

Preferably an absorbent pad is provided in the interior of the apparatus such as on the part of the walls on which no screw thread is provided. The absorbent material would be used to absorb any fragrance which may leak from the container should the membrane be punctured. The pad could be made from foam or felt with sufficient absorptive capacity to hold the maximum amount of fluid provided in the container such as 6ml in the embodiment described above.

The container may comprise any chemical agent in addition to or in place of the fragrance such as an insecticide.

The electrical connection may be adapted to meet the requirements of any electricity supply.

The filled container may comprise any suitable amount of fluid such as from 1 to 20 ml.

The heater means may be embedded any suitable distance from the surface of the lower part of the apparatus such as a distance in the range from 0.5 to 4 mm.

The apparatus may comprise any suitable material such as any sufficiently heat resistant plastics material.

The containers for the chemical agent may be disposable or re-usable.

Claims

1. An apparatus (10) for releasing a chemical agent, said apparatus having or receiving a container (46) for the chemical agent, at least a part (50) of said container (46) being operable to release the chemical agent, said part (50) being temperature sensitive wherein the apparatus (10) comprises heater means (22) for heating the container (46) and means for varying the heat supplied to the container so as to vary the emission of the chemical agent, characterised in that the means for varying the heat supplied to the container comprises at least two relatively movable co-operating parts (12, 32), one part comprising and/or secured to electric heater means (22), which part defines a base portion, and the other part comprising and/or secured to the container (46), wherein the electric heater

means is embedded in said base portion.

2. An apparatus for releasing a chemical agent as claimed in claim 1, characterised in that the co-operating parts comprise screw threads (44). 5
3. An apparatus for releasing a chemical agent as claimed in claim 1 or claim 2, characterised in that the heater means (22) comprises at least one resistor. 10
4. An apparatus for releasing a chemical agent as claimed in any preceding claim, characterised in that the heater means (22) comprises a light output device (26) which acts as a power indicator and a fuse. 15
5. An apparatus for releasing a chemical agent as claimed in any preceding claim, characterised in that the means for varying the heat supplied to the container comprises means for varying the distance between the heater means (22) and the container (46). 20
6. An apparatus for releasing a chemical agent as claimed in any preceding claim, characterised in that the apparatus comprises means (30) for indicating the distance between the heater means (22) and the container (46). 25
7. An apparatus for releasing a chemical agent as claimed in any preceding claim, characterised in that the apparatus comprises an absorbent material in order to absorb any chemical agent which may leak from the container. 30
8. An apparatus for releasing a chemical agent as claimed in any preceding claim, characterised in that the chemical agent comprises at least one of a fragrance or an insecticide. 35

Patentansprüche

1. Vorrichtung (10) zum Freisetzen eines chemischen Mittels, wobei die Vorrichtung einen Behälter (46) für das chemische Mittel enthält bzw. aufweist, mindestens ein Teil (50) des Behälters (46) so betreibbar ist, dass das chemische Mittel freigesetzt wird, das Teil auf Temperatur reagiert, und die Vorrichtung (10) eine Heizung (22) zum Erwärmen des Behälters (46) aufweist sowie eine Vorrichtung zur Änderung der dem Behälter zugeführten Wärme, so dass sich die Abgabe des chemischen Mittels verändert, dadurch gekennzeichnet, dass die Vorrichtung zum Verändern der dem Behälter zugeführten Wärme mindestens zwei zueinander bewegliche, kooperierende Teile (12, 32) umfasst, wobei ein Teil eine elektrische Heizung (22) umfasst und/oder an ihm befestigt ist und einen 45

Bodenabschnitt definiert, und der andere Teil den Behälter (46) umfasst und/oder an ihm befestigt ist, wobei die elektrische Heizung im Bodenabschnitt aufgenommen ist.

2. Vorrichtung zum Freisetzen eines chemischen Mittels nach Anspruch 1, dadurch gekennzeichnet, dass die kooperierenden Teile Gewinde (44) aufweisen.
3. Vorrichtung zum Freisetzen eines chemischen Mittels nach Anspruch 1 oder 2, dadurch gekennzeichnet, dass die Heizung (22) mindestens einen Widerstand umfasst.
4. Vorrichtung zum Freisetzen eines chemischen Mittels nach einem vorhergehenden Anspruch, dadurch gekennzeichnet, dass die Heizvorrichtung (22) eine Leuchtanzeige (26) umfasst, die als Betriebsanzeige und Sicherung dient.
5. Vorrichtung zum Freisetzen eines chemischen Mittels nach einem vorhergehenden Anspruch, dadurch gekennzeichnet, dass die Vorrichtung zum Verändern der dem Behälter zugeführten Wärme eine Vorrichtung umfasst, die die Entfernung zwischen der Heizvorrichtung (22) und dem Behälter (46) verändert.
6. Vorrichtung zum Freisetzen eines chemischen Mittels nach einem vorhergehenden Anspruch, dadurch gekennzeichnet, dass die Vorrichtung eine Vorrichtung (30) zum Anzeigen der Entfernung zwischen der Heizvorrichtung (22) und dem Behälter (46) umfasst.
7. Vorrichtung zum Freisetzen eines chemischen Mittels nach einem vorhergehenden Anspruch, dadurch gekennzeichnet, dass die Vorrichtung ein Absorptionsmittelmaterial umfasst, mit dem chemische Mittel, die aus dem Behälter auslaufen, absorbiert werden.

8. Vorrichtung zum Freisetzen eines chemischen Mittels nach einem vorhergehenden Anspruch, dadurch gekennzeichnet, dass das chemische Mittel mindestens einen Duftstoff oder ein Insektizid umfasst.

Revendications

1. Appareil (10) pour libérer un agent chimique, ledit appareil ayant ou recevant un conteneur (46) pour l'agent chimique, au moins une partie (50) dudit conteneur (46) pouvant être actionnée de façon à libérer l'agent chimique, ladite partie (50) étant sensible à la température, l'appareil (10) comprenant un moyen de chauffage (22) pour chauffer le conteneur (46) et un moyen pour faire varier la chaleur 50

amenée au conteneur de façon à modifier l'émission de l'agent chimique, caractérisé en ce que le moyen pour faire varier la chaleur amenée au conteneur comprend au moins deux parties coopérant en mobilité relative (12, 32), une de ces parties 5 comprenant un moyen de chauffage électrique (22) et/ou étant fixée sur celui-ci, cette partie définissant une partie de base, et l'autre partie comprenant le conteneur (46) et/ou étant fixée sur celui-ci, appareil dans lequel le moyen de chauffage électrique 10 est logé dans ladite partie de base.

2. Appareil pour libérer un agent chimique selon la revendication 1, caractérisé en ce que les parties coopérant comprennent des filets (44). 15
3. Appareil pour libérer un agent chimique selon la revendication 1 ou la revendication 2, caractérisé en ce que le moyen de chauffage (22) comprend au moins une résistance. 20
4. Appareil pour libérer un agent chimique selon l'une quelconque des revendications précédentes, caractérisé en ce que le moyen de chauffage (22) comprend un dispositif de sortie de lumière (26) qui 25 agit comme indicateur de puissance et fusible.
5. Appareil pour libérer un agent chimique selon l'une quelconque des revendications précédentes, caractérisé en ce que le moyen pour faire varier la chaleur amenée au conteneur comprend un moyen pour modifier la distance entre le moyen de chauffage (22) et le conteneur (46). 30
6. Appareil pour libérer un agent chimique selon l'une 35 quelconque des revendications précédentes, caractérisé en ce qu'il comprend un moyen (30) pour indiquer la distance entre le moyen de chauffage (22) et le conteneur (46). 40
7. Appareil pour libérer un agent chimique selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il comprend un matériau absorbant de façon à absorber n'importe quel agent chimique qui peut s'échapper du conteneur. 45
8. Appareil pour libérer un agent chimique selon l'une quelconque des revendications précédentes, caractérisé en ce que l'agent chimique comprend au moins un parfum ou un insecticide. 50

55

